

Motor Protection Circuit Breakers and Motor Circuit Protectors

Accessories

Description		Operator Position *			Term. No.	Description	Connection Diagram * ⊛	For Use With	Cat. No.
		OFF	ON	Tripped					
		O	X	O	13-14	N.O. Aux		140M-C, D, F; 140U-D (UL489 only in combination with 140M-C-AFC)	140M-C-AFA10
		X	O	X	11-12	N.C. Aux			140M-C-AFA01
	Front-Mounted Auxiliary Contact • 1-pole or 2-pole • No additional space required • Only 1 per device	O	X	O	13-14	N.O. Aux		140M-C, D, F; 140U-D (UL489 only in combination with 140M-C-AFC)	140M-C-AFA11
		X	O	X	21-22	N.C. Aux			
		O	X	O	13-14	N.O. Aux			140M-C-AFA20
		O	X	O	23-24	N.O. Aux			
		X	O	X	11-12	N.C. Aux			140M-C-AFA02
		X	O	X	21-22	N.C. Aux			
	Right Side-Mounted Auxiliary Contact • 2-pole • Adds 9 mm to the width of the device • Two per MPCB	O	X	O	33-34	N.O. Aux		140M-C, D, F	140M-C-ASA20
		O	X	O	43-44	N.O. Aux			
		X	O	X	31-32	N.C. Aux			140M-C-ASA02
		X	O	X	41-42	N.C. Aux			
		O	X	O	33-34	N.O. Aux			140M-C-ASA11
		X	O	X	41-42	N.C. Aux			

* X = Contact Closed; O = Contact Open

⊛

